BigTwin SuperServer SYS-621BT-HNTR

2U 4-Node BigTwin with 3 hot-swap 3.5" NVMe/SATA drives per node

More details here

Key Applications

Hyperconverged Infrastructure, Container Storage, Scale-Out File Server,

Key Features




- Socket E (LGA 4677) support 5th/4th Gen Intel® Xeon® Scalable processors;
- Intel® C741;
- 16 DIMM Slots supporting up to 4TB of memory; ECC RDIMMs up to DDR5-5600;
- Internal PCIe 4.0 x8 for 2 M.2 NVMe support onboard
  2 PCIe 5.0 x16 (LP) slot; Tool-less support
  Optional M.2 (22x80) HW RAID1 NVMe Boot Controller via SCC-A2NM2241G3-B1;
- Network connectivity via AIOM (OCP 3.0 compliant);
- 3 hot-swap 3.5" drive bays (2x PCIe 5.0 NVMe/SATA and 1x PCIe 4.0 NVMe/SATA);
- Liquid Cooling Support
  4 cooling fans per 2U enclosure, 14.9K RPM; Shared Cooling Design;
- 3000W Redundant Power Supplies Titanium Level (96%+); Shared Power Design;
- Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:;

Form Factor	2U Rackmount Enclosure: 449 x 88 x 774mm (17.68" x 3.47" x 30.5") Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")
Processor	Dual Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors Supports Intel Xeon CPU Max Series with high bandwidth memory (HBM) Up to 64C/128T; Up to 320MB Cache per CPU
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 3 bay(s) • 2 front hot-swap 3.5" PCIe 5.0 NVMe/SATA drive bay(s) • 1 front hot-swap 3.5" PCIe 4.0 NVMe/SATA drive bay(s) M.2: 2 M.2 PCIe 4.0 x4 NVMe slot(s) (M-key 22110(default); VROC required for RAID)
Expansion Slots	Default • 2 PCIe 5.0 x16 LP slot(s)
On-Board Devices	Chipset: Intel® C741 Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s) USB: 2 USB 3.0 Gen2 Type-A port(s) (Rear) Video: 1 VGA port(s)


©2024 Copyright Super Micro Computer, Inc. All rights reserved. *Product specifications may change without notice

(Front View – System)



Drive Bay (Node A-D)	Description
0 – 1	2x 3.5" Hot-Swap NVMe Gen5 (CPU1)/SATA Drive Bays
2	1x 3.5" Hot-Swap NVMe Gen4 (CPU2)/SATA Drive Bays

(Rear View – System)



Slot (Node A-D)	Description
A1	PCIe 5.0 x16 AIOM Slot
1	PCIe 5.0 x16 (LP) Slot
2	PCIe 5.0 x16 (LP) Slot

System Cooling	Fans: 4x 14.9K RPM Heavy Duty 8cm Fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)
Power Supply	2x 3000W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment CPU: Monitors for CPU Cores, Chipset Voltages, Memory. 8+4 Phase-switching voltage regulator
Dimensions and Weight	Weight: Gross Weight: 96.6 lbs (43.8 kg) Net Weight: 66.1 lbs (30 kg) Available Color: Black front & silver body
Operating Environment	RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	**Super X13DET-B**
Chassis	**CSE-827BQ2-R3K04P**

©2024 Copyright Super Micro Computer, Inc. All rights reserved. *Product specifications may change without notice