

Eaton 93PX15KIPM

Catalog Number: 93PX15KIPM

Eaton 93PX 15kW Power Module, 15 kVA/15 kW, rack or tower mount, 3U, configurable for 3 phase or 1 phase input/output

General Specifications



Photo is representative

Product Name

Eaton 93PX UPS

Product Length/Depth

802 mm

Product Width

438 mm

Compliances

CE Marked
RoHS Compliant
CB

EAN

6430070723891

Catalog Number

93PX15KIPM

Product Height

129 mm

Product Weight

24.8 kg

Certifications

IEC/EN 62040-2
IEC/EN 62040-1
EN 62040-3
Manufactured in a plant certified to ISO 9001 and ISO 14001 management system standards

Model Code

Eaton 93PX 15kW Power Module

[Type](#)

UPS

[Audible alarms](#)

Yes

[Auto shutdown function](#)

Yes

[Internal battery included](#)

No

[Battery charger type](#)

ABM technology

[External battery connection](#)

Hardwired

[Color](#)

Black

[Communication](#)

USB port (HID compliant)

Serial port (RS232)

Mini terminal block for
remote On/Off

Mini-terminal block for
remote power off

Dry contacts (4 outputs,
relay, DB9)

DB15 for parallel operation

[Construction type](#)

482.6 mm (19 inch) device

[Efficiency \(eco-mode\)](#)

99 %

[Improved efficiency mode](#)

ESS

[Number of communication slots](#)

1

[Feed type](#)

AC

[Form factor](#)

Rack/tower

[Application notes](#)

[Runtime graph - 93PX15KIPM](#)

Hot-swappable power modules

No

Input connection

Fixed connection

Input nominal voltage

380Y/220V nominal (400V/230V, 415Y/240V)

Number Of Output Connections C13

0

Number Of Output Connections C19

0

Number of output connections fixed connection

1

Output frequency

50 Hz (50/60 Hz programmable)

Output power factor

1

Overall efficiency

0.96 %

Package contents

- UPS
- Quickstart guide
- Safety instructions

Parallelable

Parallel for capacity and redundancy

Number of parallel units

3

Phase (input)

3

Phase (output)

3

Potential free switch contact

No

Rack size

3U

Runtime graph

`$row.attributeValue.cdata`

Snmp

No

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Topology

Online

kVA rating

15 kVA

Wattage

15 kW

Number Of Output Connections With Protective Contact (Schuko)

0

Application

Data center/ facility/IT

Output effective power

15000 W

Transition time for full load

0 s

Efficiency (improved efficiency mode)

99 %

Voltage distortion output (linear load) - max

1 %

Communication interface

USB

RS232

Input frequency - min

50 Hz

Input frequency - max

60 Hz

Input voltage - min

220 V

Input voltage - max

415 V

Output voltage - min

220 V

Output voltage - max

415 V

Secondary Frequency Min

50 Hz

Secondary Frequency Max

60 Hz

Output apparent power

15000 VA

Primary frequency - max

60 Hz

Primary frequency - min

50 Hz

Runtime at half load

0 min

Runtime at full load

3 min

Mounting Method

Tower

Rackmount

Number of output connections French standard (Type E)

0



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

