




## Proyectores LED de exterior FORGE PRO+

Proyectores de exterior FORGE PRO+ 6500K IP65 120º 50.000h carcasa negra



| CÓDIGO                 | 176050        | 176100        | 176150        | 176200        |
|------------------------|---------------|---------------|---------------|---------------|
| EAN                    | 8420738314828 | 8420738314835 | 8420738314842 | 8420738314859 |
| <b>CARACTERÍSTICAS</b> |               |               |               |               |
| Potencia               | 50W           | 100W          | 150W          | 200W          |
| Flujo luminoso         | 8750lm        | 17500lm       | 26250lm       | 35000lm       |
| Rendimiento            | 175lm/W       | 175lm/W       | 175lm/W       | 175lm/W       |
| Ángulo de apertura     | 120°          | 120°          | 120°          | 120°          |
| Temperatura            | 6500K         | 6500K         | 6500K         | 6500K         |
| Alimentación           | 220V-240V     | 220V-240V     | 220V-240V     | 220V-240V     |
| PF                     | 0,9           | 0,9           | 0,9           | 0,9           |
| Protección IP/IK       | IP65-IK08     | IP65-IK08     | IP65-IK08     | IP65-IK08     |
| Uso                    | Exterior      | Exterior      | Exterior      | Exterior      |
| Vida                   | 50.000h       | 50.000h       | 50.000h       | 50.000h       |
| IRC                    | >80           | >80           | >80           | >80           |
| Medidas (mm)           | 183x169x34    | 253x242x40    | 328x295x43    | 402x349x44    |
| Carcasa                | Aluminio      | Aluminio      | Aluminio      | Aluminio      |
| Acabado                | Negro         | Negro         | Negro         | Negro         |



## Proyectores LED de exterior FORGE PRO+

Proyectores de exterior FORGE PRO+ 3000k IP65 120º 50.000h carcasa negra



| CÓDIGO             | 176051        | 176101        | 176151        | 176201        |
|--------------------|---------------|---------------|---------------|---------------|
| EAN                | 8420738314989 | 8420738314996 | 8420738315009 | 8420738315016 |
| CARACTERÍSTICAS    |               |               |               |               |
| Potencia           | 50W           | 100W          | 150W          | 200W          |
| Flujo luminoso     | 8750lm        | 17500lm       | 26250lm       | 35000lm       |
| Rendimiento        | 175lm/W       | 175lm/W       | 175lm/W       | 175lm/W       |
| Ángulo de apertura | 120°          | 120°          | 120°          | 120°          |
| Temperatura        | 3000K         | 3000K         | 3000K         | 3000K         |
| Alimentación       | 220V-240V     | 220V-240V     | 220V-240V     | 220V-240V     |
| PF                 | 0,9           | 0,9           | 0,9           | 0,9           |
| Protección IP/IK   | IP65-IK08     | IP65-IK08     | IP65-IK08     | IP65-IK08     |
| Uso                | Exterior      | Exterior      | Exterior      | Exterior      |
| Vida               | 50.000h       | 50.000h       | 50.000h       | 50.000h       |
| IRC                | >80           | >80           | >80           | >80           |
| Medidas (mm)       | 183x169x34    | 253x242x40    | 328x295x43    | 402x349x44    |
| Carcasa            | Aluminio      | Aluminio      | Aluminio      | Aluminio      |
| Acabado            | Negro         | Negro         | Negro         | Negro         |