

Highlights:

- EN50399 CPR Euroclass Cca-s1b,d0,a1
- 11 AWG (4 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant

Product information:

The CLS240-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.


More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Product Features:

Application	AV & IT
Series	Contractor Series

Physical Characteristics:

Type of cable		2-core loudspeaker cable	
EN50399 CPR Euroclass		Cca-s1b,d0,a1	
Inner conductor	Material	BC 48 x 0.31 mm (Ø) (OFC)	
	Section	0.0062 "²	
		Number of conductors	2
		Insulation	Material
		Polyolefin 4 mm (Ø)	
Filling		None	
Separator		None	
Inner conductor	American Wire Gauge	11 AWG	
	Insulation	Colours	Red / Blue
		Conductor twisting	Yes
Outer jacket	Material	Polyolefin 10.2 mm (Ø)	
	Colours	Black	

Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
CPR Euroclass	Cca-s1b,d0,a1
Flammability test	According EN 60332-1-2
Indoor / outdoor	UV resistant (UL1581, UVA, 720 h)
Smoke emissions	According IEC 61034
Zero halogen compounds	According EN 50267-2-1
	IEC 60754


Electrical Characteristics:

Max. conductor	DC resistance	4.95 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Mechanical Characteristics:

Temperature range	Mobile installation	- 41 °F till + 176 °F
	Fixed installation	- 59 °F till + 176 °F
UV resistant	Yes	

Cross sections:



Variants:

- CLS240-CCA/1 - 100 m wooden reel
- CLS240-CCA/3 - 300 m wooden reel