

MPN: FPD92LULU-1000

LinkIT Fiber Cord OS2 LC/LC 100m

Duplex, SM, LSZH, Yellow

This OS2 Duplex fiber optic cable is available in several colours and lengths, and has LC connectors with UPC polishing at both ends. The cable is designed for singlemode applications with a core diameter of 9/125 µm, and supports wavelengths of 1310/1550 nm. It has low insertion loss of ≤0.3 dB and an optical return loss of ≥55 dB. The cable has a diameter of 2 mm and is covered with LSZH material, which provides flame-retardant and halogen-free properties in accordance with IEC safety standards. It withstands temperatures from -40° to +75°C, has a bend radius of 20 mm and a tensile strength of 150N. Certified according to CE and RoHS standards.



Specifications

Features	Cable length	100 m
	Cable type	Duplex
	Connector 1	LC/UPC
	Connector 1 gender	Male
	Connector 2	LC/UPC
	Connector 2 gender	Male
	Fibre optic type	G.652D
	Full duplex	Yes
	Product colour	Yellow
Legal Information	ADR Information	No restrictions
	Country of Origin	Vietnam
	Tariff No.	8544700099
	UNSPSC Code	26121607
Package dimensions	Depth (package,cm)	40 cm
	Gross Weight (Package, kg)	0.73 kg
	Height (package,cm)	6.3 cm
	Width (package,cm)	28 cm
Vendor information	Brand Name	LinkIT

Other products in this series

Cable length	Red	Yellow
0.25		FPD92LULU-0025
0.5	FPD92LULU-005-RED	FPD92LULU-005
0.7		FPD92LULU-007
1	FPD92LULU-010-RED	FPD92LULU-010
1.5		FPD92LULU-015
2	FPD92LULU-020-RED	FPD92LULU-020
2.5		FPD92LULU-025
3	FPD92LULU-030-RED	FPD92LULU-030
4		FPD92LULU-040
5	FPD92LULU-050-RED	FPD92LULU-050
6		FPD92LULU-060
7		FPD92LULU-070
8		FPD92LULU-080
9		FPD92LULU-090
10		FPD92LULU-100
12		FPD92LULU-120
13		FPD92LULU-130
14		FPD92LULU-140
15		FPD92LULU-150
20		FPD92LULU-200
25		FPD92LULU-250
30		FPD92LULU-300
35		FPD92LULU-350
40		FPD92LULU-400
45		FPD92LULU-450
50		FPD92LULU-500
55		FPD92LULU-550
65		FPD92LULU-650
75		FPD92LULU-750
100		FPD92LULU-1000
200		FPD92LULU-2000

Other images

