

MPN: SUTPC6A-2000M-GY

LinkIT SlimPatch U/UTP Cat6A Grey

20m AWG 28/7, LSZH, 3,6mm

LinkIt Patch Cat.6a cables stand out with their impressive 50-micron gold plating, which provides outstanding corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, which enables robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points and other devices that require additional power.

The modular plug is equipped with a tanglefree lock that prevents annoying cable tangles and ensures a hassle-free connection experience. The cable is supplied with a high-quality clear plug, which provides extra strength and protection to the cable ends and ensures durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI / TIA-568-C.2 and ISO 11801).



Specifications

Certificates	Certification	CE; RoHS
Features	Cable class	Cat.6a Slim
	Cable length	20 m
	Cable shielding	U/UTP (UTP)
	Cable standard	Cat6a
	Cable type	U/UTP
	Connector 1	RJ45
	Connector 1 gender	Male
	Connector 2	RJ45
	Connector 2 gender	Male
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Grey
Legal Information	ADR Information	No restrictions
	Country of Origin	China
	Tariff No.	8544200090
	UNSPSC Code	26121609
Package dimensions	Depth (package,cm)	2.5 cm
	Gross Weight (Package, kg)	0.35 kg
	Height (package,cm)	20.3 cm
	Width (package,cm)	22.8 cm
Product dimensions	Net Weight (Product, kg)	0.264 kg
Vendor information	Brand Name	LinkIT

Other products in this series

Cable length	Black	Blue	Green	Grey
0.2	SUTPC6A-0020M-SV	SUTPC6A-0020M-BL	SUTPC6A-0020M-GR	SUTPC6A-0020M-GY
0.3	SUTPC6A-0030M-SV	SUTPC6A-0025M-BL	SUTPC6A-0025M-GR	SUTPC6A-0025M-GY
0.5	SUTPC6A-0050M-SV	SUTPC6A-0050M-BL	SUTPC6A-0050M-GR	SUTPC6A-0050M-GY
0.75	SUTPC6A-0075M-SV			SUTPC6A-0075M-GY
1	SUTPC6A-0100M-SV	SUTPC6A-0100M-BL	SUTPC6A-0100M-GR	SUTPC6A-0100M-GY
1.5	SUTPC6A-0150M-SV	SUTPC6A-0150M-BL	SUTPC6A-0150M-GR	SUTPC6A-0150M-GY
2	SUTPC6A-0200M-SV	SUTPC6A-0200M-BL	SUTPC6A-0200M-GR	SUTPC6A-0200M-GY
3	SUTPC6A-0300M-SV	SUTPC6A-0300M-BL	SUTPC6A-0300M-GR	SUTPC6A-0300M-GY
5	SUTPC6A-0500M-SV	SUTPC6A-0500M-BL	SUTPC6A-0500M-GR	SUTPC6A-0500M-GY
7.5	SUTPC6A-0750M-SV	SUTPC6A-0750M-BL	SUTPC6A-0750M-GR	SUTPC6A-0750M-GY
10	SUTPC6A-1000M-SV	SUTPC6A-1000M-BL		SUTPC6A-1000M-GY
15	LI-SC6AUUTP-1500-SV			SUTPC6A-1500M-GY
20	LI-SC6AUUTP-2000-SV			SUTPC6A-2000M-GY

Cable length	Red	White	Yellow
0.2	SUTPC6A-0020M-RD	SUTPC6A-0020M-WH	SUTPC6A-0020M-YL
0.3	SUTPC6A-0025M-RD	SUTPC6A-0025M-WH	SUTPC6A-0030M-YL
0.5	SUTPC6A-0050M-RD	SUTPC6A-0050M-WH	SUTPC6A-0050M-YL
0.75		SUTPC6A-0075M-WH	SUTPC6A-0075M-YL
1	SUTPC6A-0100M-RD	SUTPC6A-0100M-WH	SUTPC6A-0100M-YL
1.5	SUTPC6A-0150M-RD	SUTPC6A-0150M-WH	SUTPC6A-0150M-YL
2	SUTPC6A-0200M-RD	SUTPC6A-0200M-WH	SUTPC6A-0200M-YL
3	SUTPC6A-0300M-RD	SUTPC6A-0300M-WH	SUTPC6A-0300M-YL
5	SUTPC6A-0500M-RD	SUTPC6A-0500M-WH	SUTPC6A-0500M-YL
7.5	SUTPC6A-0750M-RD	SUTPC6A-0750M-WH	
10		SUTPC6A-1000M-WH	
15		LI-SC6AUUTP-1500-WH	
20		LI-SC6AUUTP-2000-WH	

Other images

