

# Rittal – The System.

Faster – better – everywhere.

## Network enclosures TE 8000 – TE 7888.530

Date : Sep 19, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network enclosures TE 8000 – TE 7888.530

created: 19.09.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Benefits:</b>	No frame structure Optimum accessibility Readily dismantled and therefore easily installed
<b>Material:</b>	Sheet steel Glazed door: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Mounting frame: Dipcoat-primed Enclosure panels: Powder-coated
<b>Colour:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 20
<b>Supply includes:</b>	Self-supporting 482.6 mm (19") mounting frames, front and rear, depth-variable Glazed door at the front, including 130° hinge, designer handle and security lock 3524 E Sheet steel door at the rear, including 130° hinge, security lock 3524 E Base frame with maximum cut-out (for optional population with module plates) Roof plate including concealed cut-out for cable entry and optional fan 4 levelling feet, M10 (supplied loose) 4 spacers, 20 mm (supplied loose) to raise the roof plate 2 Side panels, lockable, including security lock 3524 E
<b>Basic material:</b>	Sheet steel

## Product features

<b>Dimensions:</b>	Width: 800 mm Height: 2000 mm Depth: 800 mm
--------------------	---

<b>Installation height for components:</b>	42 U
<b>Distance between levels as delivered:</b>	495 mm
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	116 kg
<b>EAN:</b>	4028177801462
<b>Customs tariff number:</b>	94032080
<b>ETIM 6.0:</b>	EC002499
<b>ETIM 5.0:</b>	EC002499
<b>eCl@ss 8.0/8.1:</b>	27180207
<b>eCl@ss 7.0/7.1:</b>	27180207
<b>eCl@ss 6.0/6.1:</b>	27180207
<b>eCl@ss 5.1/5.1.4:</b>	27180201

## Approvals

**Declarations:**  [Declaration of conformity \(EN, DE\)](#)

## Downloads

**Documentation:**  [Instructions \(FR, EN, DE\)](#)