

MultiSync® BT421

LCD 42" Stretched Large Format Display

Datasheet



Where space is limited but not your message

Delivering space efficient visualisation for constricted environments such as corridors and retail shelves, this 42" bartype display offers a distinctive ultra-wide 16:4 screen ratio. High adaptability extends to both landscape and portrait orientation ideal for space-limited areas, yet content creation remains easy and effortless. Content is crisp and clear with compelling readability even in bright ambient light conditions with high brightness levels of 700 cd/m² combined with an anti-glare surface. Its modern, slim design forms an elegant digital surface which perfectly complements the surrounding architecture and integrates seamlessly into any environment.

The 42" MultiSync® BT421 is the super wide choice for space efficient digital signage in retail environments, transportation hubs, quick service restaurants and all other public areas where space is limited.

Benefits

Space efficient display solution – the ultra-wide screen ratio of 16:4 with a display height of just 28.9 cm allows installation within constricted spaces, providing crisp and eye-friendly visualisation.

Robust and reliable – sealed to prohibit dust ingress, long term reliable operation is maintained within wide temperature range of 0-50°C.

Easy content adaption – the integrated trim function enables 16:9 content to be used whilst actively displaying the upper or lower area for display of native 1920 x 480 content.

Cost efficient media playback flexibility – divide a single Full HD content into two separate contents via daisy chaining for back to back installations, needing only one source to feed two screens for cost saving benefits.

Superb readability in bright light environments – crisp playback of content thanks to high brightness output of 700 cd/m² and anti-reflective screen surface delivers clearly visible messages even under varying and demanding ambient conditions.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

Product Name	MultiSync® BT421
Product Group	LCD 42" Stretched Large Format Display
Order Code	60004365

Display

Panel Technology	VA with Direct LED backlights
Active Screen Area (W x H) [mm]	1,039.7 x 259.9
Screen Size [inch/cm]	42 / 107.2
Aspect Ratio	16:4
Pixel Pitch [mm]	0.542
Brightness [cd/m²]	700
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1,073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	Pro (44)
TNi [°C]	110
Supported Orientation	Landscape; Portrait

Resolution

Native Resolution	1920 x 480			
Supported Resolutions	1920 x 1200;	1600 x 1200;	1280 x 1024;	800 x 600;
	1920 x 1080;	1440 x 900;	1280 x 800;	640 x 480
	1920 x 960;	1400 x 1050;	1280 x 768;	
	1920 x 480;	1366 x 768;	1280 x 720;	
	1680 x 1050;	1360 x 768;	1024 x 768;	

Connectivity

Input Video Digital	2 x DVI-D (with HDCP)
Input Control	LAN 100Mbit; RS232
Output Video Digital	1 x DVI-D

Electrical

Power Consumption Eco/max. [W]	50 shipping; 75 (max.)
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS

Environmental Conditions

Operating Temperature [°C]	+0 to +50
Operating Humidity [%]	20 to 90

Mechanical

Dimensions (W x H x D) [mm]	1,059.9 x 288.9 x 64.7
Weight [kg]	9.3
Bezel Width [mm]	14.7 (bottom); 7.9 (left and right); 9.8 (top)
VESA Mounting [mm]	200 x 100 (FDMI); 4 holes; 400 x 100 (FDMI); M6

Available Options

Accessories	Ceiling Mount (PDC BT S(single sided); PDC BT D (dual sided); PD Pole S, PD Pole M, PD Pole L, PD Pole XL); Wall mount (PDW BT L)
-------------	---

Green Features

Energy Efficiency	Energy efficiency class: C
-------------------	----------------------------

Additional Features

Special Characteristics	NaViSet Administrator 2; Trim Function
Safety and Ergonomics	CE; REACH; RoHS; SASO
Warranty	3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension
Operating Hours	24/7



CE



RoHS

This document is © 2020 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 22.04.2020