



Product: [3079ANH](#) 

Profibus DP, 1PR #22 Sol BC, PO ins, F/B, LSNH Jkt, 300 V



Product Description

Profibus DP, 1 Pair AWG 22 Bare Copper - Solid, Polyolefin (PO, PE, PP) insulation, Foil + Braid(s) shielding, LSZH / FRNC jacket , 300 V

Technical Specifications

Product Overview

Suitable Applications:	Instrumentation and computer cable; For data transmission applications such as Profibus
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
22	Solid	BC - Bare Copper	1

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene (Foam)	2.51 mm	0.09 mm

Color Chart

Number	Color
Pair 1	Red & Green

Outer Shield

Type	Material	Material Trade Name	Coverage [%]	Thickness of Foil
Tape	Bi-Laminate (Alum+Poly)	Beldfoil® (Z-Fold®)	100%	25 / 50 µm
Braid	Tinned Copper (TC)		65%	

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	8 mm	1.1 mm

Construction and Dimensions

Cabling

Description	Filler
1 pair and 2 fillers twisted to cable core	Flame retardant Polypropylene (2x) (2.54 mm)

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
52 Ohm/km

Capacitance

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Conductor
----------------------------	---

1 pF/m	27.9 pF/m
--------	-----------

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
3 - 20 MHz	150 Ohm	15 Ohm

Delay

Nominal Velocity of Propagation (VP) [%]
78%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)
0.2 MHz	0.9 dB/100m
4 MHz	2.2 dB/100m
16 MHz	4.5 dB/100m

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temperature Range:	-15°C To +80°C
Storage Temperature Range:	-45°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Max. Pull Tension:	220 N
Min. Bend Radius During Installation:	80 mm

Standards

CPR Euroclass:	Eca
CENELEC Compliance:	EN 50290-2-20

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
----------------------	------------------------

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2, IEC 60332-3-24
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	EAN
3079ANH.00500	Chrome	Reel	500 m	8719605005755
3079ANH.001000	Chrome	Reel	1,000 m	8719605005748
3079ANH.02500	Violet	Reel	500 m	8719605005779
3079ANH.011000	Violet	Reel	1,000 m	8719605005762

History

Update and Revision:	Revision Number: 0.246 Revision Date: 04-30-2024
----------------------	--

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.