BigTwin SuperServer SYS-620BT-HNC8R

2U BigTwin with 3 3.5" NVMe/SAS/SATA drives per node

More details here

Key Applications

Hyperconverged Infrastructure, Scale-Out File Storage, Container Storage,


Key Features




- Socket P+ (LGA 4189) support 3rd Gen Intel® Xeon® Scalable processors;
- Intel® C621A;
- 20 DIMM Slots (16 DIMM Slots + 4 Intel® Optane™ Persistent Memory Slots);
- 2 PCIe 4.0 x16 (LP) slot; Tool-less support
  Optional HW RAID Boot Controller via AOC-SMG3-2M2-B (NVMe Only)
  Internal PCIe 3.0 for 2 x4 M.2 NVMe/SATA support onboard;
- Network connectivity via AIOM (OCP 3.0 compliant);
- 3 Hot-swap 3.5" drive bays; 3 PCIe 4.0 NVMe/SAS/SATA 3.5" drives;
- 4 cooling fans per 2U enclosure, 14.9K RPM; Shared Cooling Design;
- 2600W Redundant Power Supplies Titanium Level (96%+); Shared Power Design;
- Built-in SAS3 Support via Broadcom 3808; IT Mode;
- Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:;

Form Factor	2U Rackmount Enclosure: 449 x 88 x 774mm (17.68" x 3.47" x 30.5") Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")
Processor	Dual Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable processors Up to 32C/64T; Up to 48MB Cache per CPU
System Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM Supports Intel® Optane™ persistent memory 200 series
Drive Bays Configuration	Default: Total 3 bay(s) • 3 front hot-swap 3.5" PCIe 4.0 NVMe/SAS/SATA drive bay(s) M.2: 2 M.2 PCIe 3.0 x4 NVMe/SATA slot(s) (M-key 2280(default); VROC required for RAID)
Expansion Slots	Default • 2 PCIe 4.0 x16 LP slot(s)
On-Board Devices	SAS: SAS (12Gbps) via Broadcom® 3808; (IT mode) Chipset: Intel® C621A Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s) USB: 2 USB 3.0 Type-A port(s) (Rear) Video: 1 VGA port(s)

©2024 Copyright Super Micro Computer, Inc. All rights reserved. *Product specifications may change without notice





System Cooling	Fans: 4x 14.9K RPM Heavy Duty 8cm Fan(s)
Power Supply	2x 2600W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment CPU: Monitors for CPU Cores, Chipset Voltages, Memory. 7+1 Phase-switching voltage regulator
Dimensions and Weight	Weight: Gross Weight: 96.6 lbs (43.8 kg) Net Weight: 66.1 lbs (30 kg) Available Color: Black
Operating Environment	RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	**Super X12DPT-B6**
Chassis	**CSE-827BQ-000NP**

©2024 Copyright Super Micro Computer, Inc. All rights reserved. *Product specifications may change without notice