



## USB 3.2 Gen 2x2 NVMe M.2 SSD Enclosure

No.: 43318

Convert your NVMe M.2 SSD to a portable USB 3.2 drive

#### Description

- Aluminium enclosure for PCIe/NVMe based M.2 SSD (not included)
- USB 3.2 Gen 2x2 standard with SuperSpeed USB 20Gbps data transfer rates\*
- Stylish Aluminium hosuing with special heat dissipation, ensuring a suitable operating temperature
- USB bus-powered for efficient and portable use
- 2 year warranty

The Lindy USB 3.2 Gen 2x2 NVMe M.2 SSD Enclosure allows the user to install a PCIe/NVMe based M.2 SSD as a portable external drive to USB devices like laptops or PCs. Support for the USB 3.2 Gen 2x2 standard guarantees SuperSpeed 20Gbps data transfer rates. UASP support also ensures faster speeds for UASP enabled computers.

This Lindy enclosure is compatible with PCle/NVMe based M.2 SSDs with M key in 30, 42, 60 and 80mm lengths. USB bus-powered, therefore requiring no external power supply, ensures this enclosure is an ideal portable solution for IT professionals on-the-go. The enclosure has a robust and elegant aluminium design for better heat dissipation.

\* "Please note that that 20Gbps full support is only possible with a USB 3.2 2x2 host controller"

# Technical details

#### **Specifications**

- Interface: USB to PCIe/NVMe M.2 SSD
- Interface Standard: USB 3.2 Gen 2x2, PCIe 3.0 x4
- Supported Bandwidth: 20Gbps
- Chipset: ASM2364
- Compatibility: USB Type C equipped computers (incl. Apple M1)
   Special Features: supports 30/42/60/80mm SSDs, UASP & TRIM

#### Connectors

- Inputs: 1 x USB Type C (Female)
- Outputs: 1 x PCle based M.2 (Female), M key
- Power: Bus-powered

## **Physical Properties**

- Dimensions WxDxH: 118.5x15x46mm (4.67x0.59x1.81in)
- (Fixed) Cable Length: 0.26m (0.85ft)

- Housing Material: Aluminium
  Net Weight: 0.11kg (0.24lb)
  Operating Temperature: 0°C 50°C (32°F 122°F)
  Storage Temperature: -10°C 70°C (-14°F 158°F)
  Humidity: 50 90% RH (non-condensing)
- Power Requirements: -Colour: Silver

#### Miscellaneous

- Packaging Type: Carton Box
  Packaging Dimensions: 140x100x28mm (5.51x3.94x1.1in)
  Gross Weight: 0.18kg (0.4lb)
  Warranty (Years): 2
  Certificated: CE, FCC, RoHS & REACH, CP65

### Package Contents

- USB 3.1 NVMe M.2 SSD Enclosure
- 0.26m USB 3.2 Gen 2x2 Type C to C cable
- Thermopad
- M.2 rubber retainer
- Lindy Manual

### **Purchasing information**

- No.: 43318
- EAN: 4002888433181

© LINDY 2021